

Package ‘philr’

April 15, 2020

Type Package

Title Phylogenetic partitioning based ILR transform for metagenomics data

Version 1.12.0

Date 2017-04-07

Author Justin Silverman

Maintainer Justin Silverman <jsilve24@gmail.com>

Description PhILR is short for Phylogenetic Isometric Log-Ratio Transform.

This package provides functions for the analysis of compositional data (e.g., data representing proportions of different variables/parts). Specifically this package allows analysis of compositional data where the parts can be related through a phylogenetic tree (as is common in microbiota survey data) and makes available the Isometric Log Ratio transform built from the phylogenetic tree and utilizing a weighted reference measure.

License GPL-3

LazyData TRUE

RoxygenNote 6.1.1

Imports ape, phangorn, tidy, ggplot2, ggtree

Depends

Suggests testthat, knitr, rmarkdown, BiocStyle, phyloseq, glmnet, dplyr

VignetteBuilder knitr

biocViews ImmunoOncology, Sequencing, Microbiome, Metagenomics, Software

URL <https://github.com/jsilve24/philr>

BugReports <https://github.com/jsilve24/philr/issues>

git_url <https://git.bioconductor.org/packages/philr>

git_branch RELEASE_3_10

git_last_commit c9be279

git_last_commit_date 2019-10-29

Date/Publication 2020-04-14

R topics documented:

| | |
|----------------------------|-----------|
| annotate_balance | 2 |
| buildlrBasep | 3 |
| calculate.blw | 4 |
| clrp | 5 |
| convert_to_long | 6 |
| g.colMeans | 7 |
| g.rowMeans | 7 |
| ilrp | 8 |
| mean_dist_to_tips | 9 |
| miniclo | 10 |
| name.balance | 10 |
| named_rtree | 12 |
| name_nodenummer_conversion | 12 |
| philir | 13 |
| philirInv | 14 |
| phylo2sbp | 15 |
| shift | 16 |
| Index | 18 |

| | |
|------------------|-------------------------|
| annotate_balance | <i>annotate_balance</i> |
|------------------|-------------------------|

Description

annotate a balance oriented with respect to the PhILR transform. That is, you can specify labels for the numerator (up) and denominator (down).

Usage

```
annotate_balance(tr, coord, p = NULL, labels = c("+", "-"),
  offset = 0, offset.text = 0.03, bar = TRUE, barsize = 0.01,
  barfill = "darkgrey", geom = "text", ...)
```

Arguments

| | |
|-------------|---|
| tr | phylo object |
| coord | named internal node/balance to annotate |
| p | ggtree plot (tree layer), if NULL then a new plot will be created. |
| labels | label for the numerator and denominator of the balance respectively |
| offset | offset for bar (if bar=TRUE) from tips |
| offset.text | offset of text from bar (if bar=TRUE) or from tips (if bar=FALSE) |
| bar | logical, should bar for each clade be plotted |
| barsize | width of bar (if bar=TRUE) |
| barfill | fill of bar |
| geom | geom used to draw label (e.g., 'text' or 'label') |
| ... | additional parameters passed to geom_rect and specified geom |

Value

ggplot object

Author(s)

Justin Silverman

References

Guangchuang Yu, David Smith, Huachen Zhu, Yi Guan, Tommy Tsan-Yuk Lam. *ggtree: an R package for visualization and annotation of phylogenetic trees with their covariates and other associated data*. *Methods in Ecology and Evolution* 2016, doi:10.1111/2041-210X.12628

Examples

```
tr <- named_rtree(10)

annotate_balance(tr, 'n4', size=7)
annotate_balance(tr, 'n4', size=7, barsize=0.04, barfill='darkgreen', offset.text=0.05, color='red')
annotate_balance(tr, 'n4', bar=FALSE, size=7)
annotate_balance(tr, 'n4', bar=TRUE, size=7, labels=c('Num', 'Denom'), offset.text=.3)
annotate_balance(tr, 'n4', bar=TRUE, geom='label', size=8, offset.text=0.1)
```

buildlrBasep

Weighted ILR Contrast Matrix

Description

Weighted ILR Contrast Matrix

Usage

```
buildlrBasep(W, p)
```

Arguments

W sequential binary partition matrix (e.g., signary matrix; output of [phylo2sbp](#))
 p weights (should not be closed)

Value

matrix

Author(s)

Justin Silverman (adapted from `compositions::gsi.buildlrBase`)

References

J. J. Egozcue, V. Pawlowsky-Glahn (2016) *Changing the Reference Measure in the Simplex and its Weighting Effects*. *Austrian Journal of Statistics* 45(4):25-44

Examples

```
p <- seq(.1,1,by=.2)
tr <- named_rtree(5)
sbp <- phylo2sbp(tr)
buildilrBasep(sbp, p)
```

calculate.blw

Calculate Branch Length Weightings for ILR Coordinates

Description

Calculates the weightings for ILR coordinates based on branch lengths of a phylogenetic tree via a few different methods (see details).

Usage

```
calculate.blw(tree, method = "sum.children")
```

Arguments

| | |
|--------|--|
| tree | a phylo class tree object that is binary (see multi2di) |
| method | options include: (default) 'sum.children' and 'mean.descendants' see details for more information. |

Details

ILR balances built from a binary partition of a phylogenetic tree can be imbued with branch length information. This function is helpful in calculating those weightings.

There are a number of methods for calculating these weightings, the default 'sum.children' calculates the weighting for a given balance as the sum of its two direct children's branch length. An alternative that has been as yet less studied is 'mean.descendants' to calculate the weighting for a given balance as the sum of its two direct children's branch lengths PLUS for each child the average distance from it to its descendant tips.

Note: That some trees contain tips with branch lengths of zero length. This can result in that tip being unreasonably downweighted, as such this function automatically adds a small pseudocount to those tips with zero length (equal to the smallest non-zero) branch length on the tree.

Value

vector of weightings for ILR coordinates produced via specified method.

Author(s)

Justin Silverman

See Also

[philr](#)

Examples

```
tr <- named_rtree(50)
calculate.blw(tr, method='sum.children')[1:10]
calculate.blw(tr, method='mean.descendants')[1:10]
```

clrp

Weighted CLR Transform

Description

Weighted CLR Transform

Usage

```
clrp(y, p)
```

```
clrpInv(y.star)
```

Arguments

| | |
|--------|---|
| y | shifted data matrix (e.g., output of shiftp) |
| p | weights (should not be closed) |
| y.star | a data matrix that represents data transformed by clrp |

Details

Note that this function will close the dataset y to 1.

Inverting clrp transform should be followed by [shiftpInv](#) to return to unshifted original composition (see examples).

Value

matrix

Author(s)

Justin Silverman

References

J. J. Egozcue, V. Pawłowsky-Glahn (2016) *Changing the Reference Measure in the Simplex and its Weighting Effects*. *Austrian Journal of Statistics* 45(4):25-44

Examples

```

p <- seq(.1,1,by=.2)
c <- t(rmultinom(10,100,c(.1,.6,.2,.3,.2))) + 0.65 # add a small pseudocount
x <- miniclo(c)
y <- shiftp(x, p)
y.star <- clrp(y, p)
y.star

# Untransform data (note use of shiftp and miniclo to return to x)
y.closed <- clrpInv(y.star)
all.equal(miniclo(shiftpInv(y.closed, p)), x)

```

convert_to_long

Converts wide format ILR transformed data to long format

Description

Converts wide format ILR transformed data (see [philir](#)) to long format useful in various plotting functions where long format data is required.

Usage

```
convert_to_long(df, labels)
```

Arguments

df PHILR transformed data in wide format (samples by balances) (see [philir](#))
labels vector (of length nrow(df)) with labels to group samples by

Value

df in long format with columns

- sample
- labels
- coord
- value

Examples

```

tr <- named_rtree(5)
df <- t(rmultinom(10,100,c(.1,.6,.2,.3,.2))) + 0.65 # add a small pseudocount
colnames(df) <- tr$tip.label

df.philir <- philir(df, tr, part.weights='enorm.x.gm.counts',
  ilr.weights='blw.sqrt', return.all=FALSE)
convert_to_long(df.philir, rep(c('a','b'), 5))

```

| | |
|------------|-----------------------------------|
| g.colMeans | <i>Geometric Means of Columns</i> |
|------------|-----------------------------------|

Description

Calculates geometric mean of columns. Does not calculate WEIGHTED geometric means (vs. [g.rowMeans](#))

Usage

```
g.colMeans(x)
```

Arguments

x matrix or vector

Value

vector (geometric mean of columns)

See Also

[g.rowMeans](#)

Examples

```
philr:::g.colMeans(rbind(c(2,4,4), c(2,4,4)))
```

| | |
|------------|---|
| g.rowMeans | <i>Weighted Geometric Means of Rows</i> |
|------------|---|

Description

Calculates weighted geometric mean (see references). Note if `p=rep(1, nrow(y))` (default) then this is just the geometric mean of rows.

Usage

```
g.rowMeans(y, p = rep(1, nrow(y)))
```

Arguments

y shifted data matrix (e.g., output of [shiftp](#))
p weights (should not be closed)

Value

vector (weighted geometric mean of rows)

References

J. J. Egozcue, V. Pawlowsky-Glahn (2016) *Changing the Reference Measure in the Simplex and its Weighting Effects*. Austrian Journal of Statistics 45(4):25-44

See Also

[g.colMeans](#)

Examples

```
p <- seq(.1,1,by=.2)
c <- t(rmultinom(10,100,c(.1,.6,.2,.3,.2))) + 0.65 # add a small pseudocount
x <- miniclo(c)
y <- shiftp(x, p)
philr:::g.rowMeans(y, p)
```

ilrp

Weighted ILR Transform

Description

Calculated using weighted CLR transform ([clrp](#))

Usage

```
ilrp(y, p, V)
```

```
ilrpInv(y.star, V)
```

Arguments

| | |
|--------|---|
| y | shifted data matrix (e.g., output of shiftp) |
| p | weights (should not be closed) |
| V | weighted contrast matrix (e.g., output of buildilrBasep) |
| y.star | a data matrix that represents data transformed by ilrp |

Value

matrix

Author(s)

Justin Silverman

References

J. J. Egozcue, V. Pawlowsky-Glahn (2016) *Changing the Reference Measure in the Simplex and its Weighting Effects*. Austrian Journal of Statistics 45(4):25-44

See Also

[philrInv](#)

Examples

```
# Weights
p <- seq(.1,1,by=.2)

# Shifted Composition
c <- t(rmultinom(10,100,c(.1,.6,.2,.3,.2))) + 0.65 # add a small pseudocount
x <- miniclo(c)
y <- shiftp(x, p)

# Contrast Matrix
tr <- named_rtree(5)
sbp <- phylo2sbp(tr)
V <- buildilrBasep(sbp, p)

y.star <- ilrp(y, p, V)
y.star

# Untransform data (note use of shiftp and miniclo to return to x)
y.closed <- ilrpInv(y.star, V)
all.equal(miniclo(shiftpInv(y.closed, p)), x, check.attributes=FALSE)
```

| | |
|-------------------|---|
| mean_dist_to_tips | <i>Mean distance from internal nodes to descendant tips</i> |
|-------------------|---|

Description

Calculates the mean distance from each internal node to its descendant tips

Usage

```
mean_dist_to_tips(tree)
```

Arguments

tree a phylo class tree object that is binary (see [multi2di](#))

Details

This is a function used by [calculate.blw](#) when method='mean.descendants', there this function is called twice, once for each direct child of a given internal node and the results are summed for each node.

Value

vector (named if internal nodes are named)

Examples

```
tr <- named_rtree(5)
mean_dist_to_tips(tr)
```

| | |
|---------|----------------|
| miniclo | <i>miniclo</i> |
|---------|----------------|

Description

small function to close (aka normalize by proportions, aka total sum scaling) a dataset to a constant k (usually taken to be 1). After closure the row sums of the dataset should sum to k.

Usage

```
miniclo(c, k = 1)
```

Arguments

| | |
|---|----------------------|
| c | dataset to be closed |
| k | closure constant |

Value

matrix (if c is a vector or matrix) or data.frame (if c is a data.frame)

Examples

```
c <- matrix(c(1,2,3,1,2,3,1,2,3), nrow = 3, byrow=TRUE)
miniclo(c)
miniclo(c, k=2)
```

| | |
|--------------|--|
| name.balance | <i>Name a balance (coordinate) based on taxonomy</i> |
|--------------|--|

Description

For a given ILR balance (coordinate) assigns a name to the balance based on a provided taxonomy table. This is useful for interpretation of the balances.

Usage

```
name.balance(tr, tax, coord, method = "voting", thresh = 0.95,
  return.votes = NULL)
```

Arguments

| | |
|--------|---|
| tr | an object of class 'phylo' |
| tax | a matrix/data.frame of taxonomy, rownames should correspond to tr\$tip.labels columns should be taxonomic levels (named) with increasing taxonomic resolution from left to right (e.g., Phylum to the left of Genus). |
| coord | the name of a balance/internal node on the tree (given as a string) |
| method | currently only 'voting' implemented. See Details. |

| | |
|--------------|---|
| thresh | threshold for assignment of taxonomy to a given part of a balance (must be greater than 0.5 if method='voting'; see details). |
| return.votes | whether voting results by taxonomic level should be shown for coord. Note: this is helpful when name.balance does not return a clear winner, as may be the case when a given coord represents more than one taxonomic lineage. votes are returned as a list indexed by colnames(tax) Options include: NULL (default) only returns the combined consensus name of the balance 'up' adds tallied votes for the 'up' node to the output list 'down' adds tallied votes for the 'down' node to the output list 'self' adds tallied votes for coord to the output list |

Details

A bit of terminology:

coord this is the same as the names of the balances which should be the same as the names of the internal nodes of tr

'up' this is the child node of coord that is represented in the numerator of the coord balance.

'down' this is the child node of coord that is represented in the denominator of the coord balance

The method 'voting' assigns the name of the each part of a balance (e.g., numerator and denominator / each child of coord) as follows:

1. First Subset tax to contain only descendent tips of the given child of coord
2. Second At the finest taxonomic (farthest right of tax) see if any one taxonomic label is present at or above thresh. If yes output that taxonomic label (at that taxonomic level) as the label for that child of coord. If no then move to coarser taxonomic level (leftward) and repeat.

Value

If return.votes=NULL returns a string of the form (ex. 'Genus_Bacteroides/Phylum_Firmicutes'). Otherwise returns a list with the above string as 'name', see Arguments for show.votes for other optional returned items.

Author(s)

Justin Silverman

See Also

[philr](#)

Examples

```
tr <- named_rtree(40)
tax <- data.frame(Kingdom=rep('A', 40),
                 Phylum=rep(c('B','C'), each=20),
                 Genus=c(sample(c('D','F'),20, replace=TRUE),
                         sample(c('G','H'), 20, replace=TRUE)))
rownames(tax) <- tr$tip.label
name.balance(tr, tax, 'n1')
name.balance(tr, tax, 'n34')
name.balance(tr,tax, 'n34', return.votes = c('up', 'down'))
```

named_rtree

Generate random tree with named internal nodes

Description

Internal nodes are named by numbering and adding the prefix 'n'. This function is largely for use in examples throughout this package.

Usage

```
named_rtree(n)
```

Arguments

n an integer giving the number of tips in the tree.

Value

An object of class "phylo"

Examples

```
named_rtree(5)
```

name_nodenum_conversion

Convert between node/tip labels and integer node numbers

Description

Useful if you want to convert between node labels (c), tip labels (t) and the internal integer number that identifies that node (nn). Particularly for use with plotting libraries.

Usage

```
nn.to.name(tr, x)
```

```
name.to.nn(tr, x)
```

Arguments

tr object of type phylo

x vector of numerics or characters

Value

vector

Examples

```
tr <- named_rtree(5)
name.to.nn(tr, 'n1')
name.to.nn(tr,c('n1','n2','t1'))
nn.to.name(tr, 1:9)
```

phlir

*Data transformation and driver of PhILR.***Description**

This is the main function for building the phylogenetic ILR basis, calculating the weightings (of the parts and the ILR coordinates) and then transforming the data.

Usage

```
phlir(df, tree, sbp = NULL, part.weights = "uniform",
      ilr.weights = "uniform", return.all = FALSE)
```

Arguments

| | |
|--------------|---|
| df | matrix of data to be transformed (samples are rows, compositional parts are columns) - zero must be dealt with either with pseudocount, multiplicative replacement, or another method. |
| tree | a phylo class tree object that is binary (see multi2di) |
| sbp | (Optional) give a precomputed sbp matrix phylo2sbp if you are going to build multiple ILR bases (e.g., with different weightings). |
| part.weights | weightings for parts, can be a named vector with names corresponding to colnames(df) otherwise can be a string, options include: 'uniform' (default) uses the uniform reference measure 'gm.counts' geometric mean of parts of df 'anorm' aitchison norm of parts of df (after closure) 'anorm.x.gm.counts' 'anorm' times 'gm.counts' 'enorm' euclidean norm of parts of df (after closure) 'enorm.x.gm.counts' 'enorm' times 'gm.counts', often gives good results |
| ilr.weights | weightings for the ILR coordiantes can be a named vector with names corresponding to names of internal nodes of tree otherwise can be a string, options include: 'uniform' (default) no weighting of the ILR basis 'blw' sum of children's branch lengths 'blw.sqrt' square root of 'blw' option 'mean.descendants' sum of children's branch lengths PLUS the sum of each child's mean distance to its descendent tips |
| return.all | return all computed parts (e.g., computed sign matrix(sbp), part weightings (codep), ilr weightings (codeilr.weights), contrast matrix (V)) as a list (default=FALSE) in addition to in addition to returning the transformed data (df.ilrp). If return.all==FALSE then only returns the transformed data (not in list format) If FALSE then just returns list containing df.ilrp. |

Details

This is a utility function that pulls together a number of other functions in `phlr`. The steps that are executed are as follows:

1. Create `sbp` (sign matrix) if not given
2. Create parts weightings if not given
3. Shift the dataset with respect to the new reference measure (e.g., part weightings)
4. Create the basis contrast matrix from the sign matrix and the reference measure
5. Transform the data based on the contrast matrix and the reference measure
6. Calculate the specified ILR weightings and multiply each balance by the corresponding weighting

Note for both the reference measure (part weightings) and the ILR weightings, specifying 'uniform' will give the same results as not weighting at all.

Note that some of the prespecified `part.weights` assume `df` is given as counts and not as relative abundances. Except in this case counts or relative abundances can be given.

Value

matrix if `return.all=FALSE`, if `return.all=TRUE` then a list is returned (see above).

Author(s)

Justin Silverman

See Also

[phylo2sbp calculate.blw](#)

Examples

```
tr <- named_rtree(5)
df <- t(rmultinom(10,100,c(.1,.6,.2,.3,.2))) + 0.65 # add a small pseudocount
colnames(df) <- tr$tip.label

phlr(df, tr, part.weights='enorm.x.gm.counts',
      ilr.weights='blw.sqrt', return.all=FALSE)
```

phlrInv

Inverse of PhILR Transform

Description

Inverse of PhILR Transform

Usage

```
phlrInv(df.ilrp, tree = NULL, sbp = NULL, V = NULL,
        part.weights = NULL, ilr.weights = NULL)
```

Arguments

| | |
|---------------------------|--|
| <code>df.ilrp</code> | transformed data to which the inverse transform will be applied |
| <code>tree</code> | (optional) to be used to build sbp and contrast matrix (see details) |
| <code>sbp</code> | (optional) the sbp (sequential binary partition) used to build a contrast matrix (see details) |
| <code>V</code> | (optional) the contrast matrix (see details) |
| <code>part.weights</code> | weightings for parts, can be a named vector with names corresponding to <code>colnames(df)</code> . Defaults to 'uniform' (<code>part.weights = 1,...,1</code>) |
| <code>ilr.weights</code> | weightings for the ILR coordinates can be a named vector with names corresponding to names of internal nodes of <code>tree</code> . Defaults to 'uniform' (<code>ilr.weights = 1,...,1</code>) |

Details

This is a utility function for calculating the inverse of the [philr](#) transform. Note that at least one of the following parameters must be specified (`tree`, `sbp`, or `V`).

Value

a matrix of compositions (rows are samples, columns are parts), function removes the effects of `ilr` weights, `part.weights`, and unshifts the composition.

Author(s)

Justin Silverman

See Also

[philr](#)

Examples

```
tr <- named_rtree(5)
df <- t(rmultinom(10,100,c(.1,.6,.2,.3,.2))) + 0.65 # add a small pseudocount
colnames(df) <- tr$tip.label
d <- philr(df, tr, part.weights='enorm.x.gm.counts',
           ilr.weights='blw.sqrt', return.all=TRUE)
d.inverted <- philrInv(d$df.ilrp, V=d$V, part.weights = d$part.weights,
                     ilr.weights = d$ilr.weights)
all.equal(miniclo(df), d.inverted)
```

Description

This function converts a binary phylogenetic tree to sequential binary partition to be used to then build an ILR basis for compositional metagenomic data.

Usage

```
phylo2sbp(tr)
```

Arguments

tr a phylo tree object with n leaves

Details

The choice of orientation for a balance (i.e., which of the two descendant clades of an internal node is in the numerator or denominator of the log-ratio) is given by the default of the function `phangorn::Children` and that choice is used consistently throughout the `philr` package.

Value

a n by n-1 matrix of the sequential binary partition sign matrix

Author(s)

Justin Silverman

References

Schliep K.P. 2011. `phangorn`: phylogenetic analysis in R. *Bioinformatics*, 27(4) 592-593

See Also

[philr](#)

Examples

```
tr <- named_rtree(5)
phylo2sbp(tr)
```

shift

Shift data to origin given by p

Description

Shift must be applied before transformation

Usage

```
shiftp(x, p)
```

```
shiftpInv(y, p)
```

Arguments

x closed compositional data matrix (or vector)
p weights (should not be closed)
y the shifted composition output by `shiftp`

Value

shifted data matrix y (no closure is applied) rows are samples, columns are parts

Author(s)

Justin Silverman & J. J. Egozcue

References

J. J. Egozcue, V. Pawlowsky-Glahn (2016) *Changing the Reference Measure in the Simplex and its Weighting Effects*. *Austrian Journal of Statistics* 45(4):25-44

Examples

```
p <- seq(.1,1,by=.2)
c <- t(rmultinom(10,100,c(.1,.6,.2,.3,.2))) + 0.65 # add a small pseudocount
x <- miniclo(c)
shiftp(x, p)
```

Index

annotate_balance, [2](#)

build.phylo.ilr (philr), [13](#)
buildilrBasep, [3](#), [8](#)

calc.blw (calculate.blw), [4](#)
calculate.blw, [4](#), [9](#), [14](#)
clrp, [5](#), [8](#)
clrpInv (clrp), [5](#)
convert_to_long, [6](#)

g.colMeans, [7](#), [8](#)
g.rowMeans, [7](#), [7](#)

ilrp, [8](#)
ilrpInv (ilrp), [8](#)

mean_dist_to_tips, [9](#)
miniclo, [10](#)
multi2di, [4](#), [9](#), [13](#)

name.balance, [10](#)
name.to.nn
 (name_nodenum_conversion),
 [12](#)
name_nodenum_conversion, [12](#)
named_rtree, [12](#)
nn.to.name
 (name_nodenum_conversion),
 [12](#)

philr, [4](#), [6](#), [11](#), [13](#), [15](#), [16](#)
philrInv, [8](#), [14](#)
phylo2sbp, [3](#), [13](#), [14](#), [15](#)

shift, [16](#)
shiftp, [5](#), [7](#), [8](#)
shiftp (shift), [16](#)
shiftpInv (shift), [16](#)