

Package ‘derfinderHelper’

April 15, 2019

Type Package

Title derfinder helper package

Version 1.16.1

Date 2018-12-03

Depends R(>= 3.2.2)

Imports IRanges (>= 1.99.27), Matrix, methods, S4Vectors (>= 0.2.2)

Suggests sessioninfo, knitcitations (>= 1.0.1), knitr (>= 1.6),
BiocStyle (>= 2.5.19), rmarkdown (>= 0.3.3), testthat

VignetteBuilder knitr

Description Helper package for speeding up the derfinder package when using
multiple cores.

License Artistic-2.0

LazyData false

URL <https://github.com/leekgroup/derfinderHelper>

BugReports <https://support.bioconductor.org/t/derfinderHelper>

biocViews DifferentialExpression, Sequencing, RNASeq, Software,
ImmunoOncology

RoxygenNote 5.0.1

git_url <https://git.bioconductor.org/packages/derfinderHelper>

git_branch RELEASE_3_8

git_last_commit 92894af

git_last_commit_date 2018-12-03

Date/Publication 2019-04-15

Author Leonardo Collado-Torres [aut, cre],
Andrew E. Jaffe [aut],
Jeffrey T. Leek [aut, ths]

Maintainer Leonardo Collado-Torres <lcollado@jhu.edu>

R topics documented:

| | |
|-------------------------|---|
| derfinderHelper-package | 2 |
| fstats.apply | 2 |

| | |
|--------------|----------|
| Index | 5 |
|--------------|----------|

 derfinderHelper-package

derfinder helper package

Description

Helper package for speeding up the derfinder package when using multiple cores.

Author(s)

Leonardo Collado-Torres <lcollado@jhu.edu>

 fstats.apply

Calculate F-statistics per base by extracting chunks from a DataFrame

Description

Extract chunks from a DataFrame and get the F-statistics on the rows of data, comparing the models mod (alternative) and mod0 (null).

Usage

```
fstats.apply(index = Rle(TRUE, nrow(data)), data, mod, mod0, adjustF = 0,
             lowMemDir = NULL, method = "Matrix", scalefac = 32)
```

Arguments

| | |
|-----------|--|
| index | An index (logical Rle is the best for saving memory) indicating which rows of the DataFrame to use. |
| data | The DataFrame containing the coverage information. Normally stored in coveragePrep\$coveragePr from derfinder::preprocessCoverage. Could also be the full data from derfinder::loadCoverage. |
| mod | The design matrix for the alternative model. Should be m by p where p is the number of covariates (normally also including the intercept). |
| mod0 | The design matrix for the null model. Should be m by p_0. |
| adjustF | A single value to adjust that is added in the denominator of the F-stat calculation. Useful when the Residual Sum of Squares of the alternative model is very small. |
| lowMemDir | The directory where the processed chunks are saved when using derfinder::preprocessCoverage with a specified lowMemDir. |
| method | Has to be either 'Matrix' (default), 'Rle' or 'regular'. See details. |
| scalefac | The scaling factor used in derfinder::preprocessCoverage. It is only used when method='Matrix'. |

Details

If `lowMemDir` is specified then `index` is expected to specify the chunk number.

`fstats.apply` has three different implementations which are controlled by the `method` parameter. `method='regular'` coerces the data to a standard `'matrix'` object. `method='Matrix'` coerces the data to a `sparseMatrix` which reduces the required memory. This method is only usable when the projection matrices have row sums equal to 0. Note that these row sums are not exactly 0 due to how the computer works, thus leading to very small numerical differences in the F-statistics calculated versus `method='regular'`. Finally, `method='Rle'` calculates the F-statistics using the Rle compressed data without coercing it to other types of objects, thus using less memory than the other methods. However, its speed is affected by the number of samples (n) as the current implementation requires $n(n + 1)$ operations, so it's only recommended for small data sets. `method='Rle'` does result in small numerical differences versus `method='regular'`.

Overall `method='Matrix'` is faster than the other options and requires less memory than `method='regular'`. With tiny example data sets, `method='Matrix'` can be slower than `method='regular'` because the coercion step is slower.

In `derfinder` versions $\leq 0.0.62$, `method='regular'` was the only option available.

Value

A numeric Rle with the F-statistics per base for the chunk in question.

Author(s)

Leonardo Collado-Torres, Jeff Leek

Examples

```
## Create some toy data
library('IRanges')
toyData <- DataFrame(
  'sample1' = Rle(sample(0:10, 1000, TRUE)),
  'sample2' = Rle(sample(0:10, 1000, TRUE)),
  'sample3' = Rle(sample(0:10, 1000, TRUE)),
  'sample4' = Rle(sample(0:10, 1000, TRUE)))

## Create the model matrices
group <- c('A', 'A', 'B', 'B')
mod.toy <- model.matrix(~ group)
mod0.toy <- model.matrix(~ 0 + rep(1, 4))

## Get the F-statistics
fstats <- fstats.apply(data = toyData, mod = mod.toy, mod0 = mod0.toy,
  scalefac = 1)

## Example with data from derfinder package
## Not run:
## Load the data
library('derfinder')

## Create the model matrices
mod <- model.matrix(~ genomeInfo$pop)
mod0 <- model.matrix(~ 0 + rep(1, nrow(genomeInfo)))
```

```
## Run the function
system.time(fstats.Matrix <- fstats.apply(data=genomeData$coverage, mod=mod,
  mod0=mod0, method='Matrix', scalefac = 1))
fstats.Matrix

## Compare methods
system.time(fstats.regular <- fstats.apply(data=genomeData$coverage,
  mod=mod, mod0=mod0, method='regular'))
system.time(fstats.Rle <- fstats.apply(data=genomeData$coverage, mod=mod,
  mod0=mod0, method='Rle'))

## Small numerical differences can occur
summary(fstats.regular - fstats.Matrix)
summary(fstats.regular - fstats.Rle)

## You can make the effect negligible by appropriately rounding
## findRegions(cutoff) so the DERs will be the same regardless of the method
## used.

## Extra comparison, although the method to compare against is 'regular'
summary(fstats.Rle - fstats.Matrix)

## End(Not run)
```

Index

*Topic **package**

derfinderHelper-package, [2](#)

derfinderHelper-package, [2](#)

fstats.apply, [2](#), [3](#)

sparseMatrix, [3](#)